



Experience unparalleled precision with our patented absolute measuring system S_Probe P25D, designed for workshop environments, and offering Bluetooth® technology output for easy data acquisition.







High resolution

0.01 micron



Integrated wireless output

Bluetooth® technology




Long life

Ball bearing, stainless steel and IP54



BENEFITS

- Outstanding resolution: 0.01 micron
- Measuring range 25.4mm
- High Accuracy and Repeatability: Patented inductive measuring system
- Built to last in workshops: extremely robust ball bearing guide, stainless steel body and IP54 protection
- Direct output data with Bluetooth® technology
- Powered by AA battery or USB-cable*
- Saves time with Lightning-Fast Readings: up to 100 values per second



TECHNICAL DATA

		801-1626	801-1638
Measuring range	mm	25.4	
Туре		P25D Smart	P25D Smart CF
Force	Ν	0.7 - 1.3 ¹⁾	0.15 2)
Resolution	μm	0.01	
Max. error	μm	0.8	
Repeatability	μm	0.08	
Power supply		1.5V AA (LR06) battery (rechargeable 1.2V battery can be used) / 4.5 – 5.5V on USB-C port	
Output data		Bluetooth® Wireless Technology	
Protection		IP54	

^{1) ± 20%,} vertical position

APPLICATION EXAMPLES



^{*} The USB-C cable does not charge the probe, it only powers the probe.

²⁾ CF = constant force : usable only vertically, rod pointing downwards (without spring)